

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Kylarväska Super FBL

1.2 Relevant identified uses of the substance or mixture and uses advised against

Antifreeze fluid, ready-mixed

1.3 Details of the supplier of the safety data sheet

Supplier Agro Oil
Box 30192
104 25 Stockholm, Sweden
Telephone +46 (0)10-556 00 00
E-mail info@agrol.se

1.4 Emergency telephone number

Sweden

Swedish Poisons Information Centre 010-456 67 00 (Open 24/7)
Emergency 112 (Ask for the Poison Centre)

Finland

Poison Information Centre 09-471 977 (Open 24/7)
Emergency 112 (Ask for the Poison Centre)

Norway

Norwegian Poison Information Centre 22 59 13 00 (Open 24/7)
Emergency 113 (Ask for the Poison Centre)

SECTION 2. HAZARD IDENTIFICATION

2.1 Classification of the substance or mixture

Acute Tox. 4, H302
STOT RE 2, H373

2.2 Label elements

Hazard pictograms



Kylarväska Super FBL

Signal word

WARNING

Contains

Ethane-1,2-diol

Hazard statements

H302 Harmful if swallowed.
H373 May cause damage to organs (kidney) through prolonged or repeated exposure.

Precautionary statements

P102 Keep out of reach of children.
P260 Do not breathe dust/fume/ gas/mist/vapours/spray.
P301 + P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
P330 Rinse mouth.
P501 Dispose of contents/container to approved waste disposal facility in accordance with local regulations

2.3 Other hazards

Ethane-1,2-diol can easily be absorbed through the skin.

Contains anhydrous disodium tetraborate, which is on the Candidate List of substances of very high concern.

SECTION 3. COMPOSITION/INFORMATION OM INGREDIENTS

3.2 Mixtures

Classification according to Regulation (EC) No 1272/2008 [CLP]

Name	EC no.	CAS no.	REACH reg no.	% (w/w)	Hazard statements
Ethane-1,2-diol	203-473-3	107-21-1	01-2119456816-28	40 - < 50	Acute Tox. 4, H302 STOT RE 2, H373
Sodium 2-ethylhexanoate	243-283-8	19766-89-3	01-2119972937-17	1-< 2	Repr. 2, H361d
Decanedioic acid, disodium salt	241-300-3	17265-14-4	01-2120762063-61	< 2	Eye Irrit. 2, H319
Disodium tetraborate, anhydrous ¹	215-540-4	1330-43-4	01-2119490790-32	< 0,3	Eye Irrit. 2, H319 Repr 1B, H360FD

¹Listed on the EU Candidate List of substances of very high concern (SVHC)

Also contains a colourant which does not affect the classification.

Other information

For a full text of hazard statements: see Section 16

SECTION 4. FIRST AID MEASURES

4.1 Description of first aid measures

After inhalation: Fresh air and rest. If difficulties in breathing get medical advice.

Kylarväska Super FBL

After eye contact: Rinse the eyes gently with water for at least 15 minutes. If symptoms persist consult a doctor.

After skin contact: Take off contaminated clothing. Wash skin with soap and water

After ingestion: Rinse mouth and drink water. Contact a doctor if experiencing symptoms.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation: The vapours may cause dizziness, drowsiness and headache, at high concentrations.

Eye: May cause mild eye irritation.

Skin: Causes degreasing. May cause mild skin irritation..

Ingestion: Small amounts are not expected to produce any acute symptoms.

Large amounts may cause nausea and vomiting.

Repeated exposure through ingestion affects the kidneys and central nervous system and may cause headache, dizziness, nausea, vomiting, confusion and, in severe cases, unconsciousness.

4.3 Indication of any immediate medical attention and special treatment needed

-

SECTION 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Can be extinguished using dry powder, foam, carbon dioxide or water fog.

Unsuitable extinguishing media: Do not use direct water jet.

5.2 Special hazards arising from the substance or mixture

In case of fire, toxic and corrosive gases may develop.

5.3 Advice for firefighters

Precautions according to the standard procedure for chemical fires. Use water **only** to cool down containers that are exposed to fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with eyes and skin.

6.2 Environmental precautions

Do not allow discharge to enter sewers, watercourses or the ground.

6.3 Methods and material for containment and cleaning up

Contain/absorb spillages with suitable absorbent material such as sand or active clay.

Disposal of waste must be in accordance with national regulations.

6.4 Reference to other sections

See Section 8 for Exposure controls / personal protection and Section 13 for disposal considerations.

Kylarväska Super FBL

SECTION 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid prolonged or repeated contact with skin. Avoid inhalation of vapours, mist or fumes. Do not reuse soiled clothing unless laundered.

7.2 Conditions for safe storage, including any incompatibilities

Containers must be kept tightly closed and sealed, in a cool and dry place. The product is hygroscopic. Keep out of reach of children.

7.3 Specifik end use

See Section 1.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Exposure limits according to National regulations

AFS 2018:1, Sweden

Substance	Cas nr	NGV	NGV	KTV	KTV	Note	Year
		ppm	mg/m ³	ppm	mg/m ³		
Ethane-1,2-diol	107-21-1	10	25	40	104	H, 26	2015

Note:

H: The substance can be easily absorbed through the skin
26: The limit value applies to the total concentration of vapour and aerosol.

654/2020, Finland

Substance	Cas nr	HTP 8 hours		HTP 15 minutes		Note	Year
		ppm	mg/m ³	ppm	mg/m ³		
Ethane-1,2-diol	107-21-1	20	50	40	100	skin	2002

Note:

Skin: Substance where the significance of skin exposure can be very large given the total exposure.

Regulations concerning Action and Limit values, Norway

Name	Cas nr	ppm	mg/m ³	Note	Last amended
Ethane-1,2-diol	107-21-1	20 40	52 104	HE S	2012

Note:

H, E: Chemicals that can be absorbed through the skin. The EU has adopted a recommended limit value for the substance.
S: The short-term exposure limit: the average concentration of a chemical substance in an employee's breathing zone that must not be exceeded over a given reference period. The reference period is 15 minutes.

Kylarväska Super FBL

Other information

DNEL:

Ethane-1,2-diol	Worker				General public			
	Long term exposure				Long term exposure			
	Systemic effects		Local effects		Systemic effects		Local effects	
Inhalation	-	mg/m ³	35	mg/m ³	-	mg/m ³	7	mg/m ³
Dermal	106	mg/kg	-	mg/kg	53	mg/kg	-	mg/kg

PNEC:

Ethane-1,2-diol	Freshwater:	10	mg/l
	Marine water:	1	mg/l
	Intermittent release:	10	mg/l
	Sediment (freshwater):	20,9	mg/kg
	Soil:	1,53	mg/kg
	Sewage treatment plant:	199,5	mg/l

8.2 Exposure controls

Appropriate technical measures

Ensure adequate ventilation. Methods are designed to prevent direct contact.

Personal protection

Respiratory protection: Use respiratory protection when insufficient ventilation. Respiratory mask with filter A (brown).

Eye/face protection: Wear eye protection (safety glasses with side shields or full face shield) when risk of splashing.

Skin protection: Wear protective gloves (butyl rubber, nitrile or PVC) and protective clothing.

Environmental exposure control

Prevent discharges into drains.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Blue-green
Odour:	No information
Melting point / freezing point:	<-18 °C
Boiling point or initial boiling point and boiling range:	≥165 °C
Flammability:	The product is not classified as flammable but can ignite and maintain a fire.
Upper / lower flammability or explosive limits:	No information
Flash point:	>126 °C
Auto-ignition temperature:	Not self-igniting
Decomposition temperature:	No information

Kylarväska Super FBL

pH	6pprox.. 7
Kinematic viscosity:	>20 mm ² /s (20 °C)
Solubility:	Completely soluble in water.
Partition coefficient n-octanol/water:	No information
Vapour pressure	0,2 hPa (20 °C)
Density and/or relative density:	1,122 g/cm ³ (20 °C)
Relative vapour density:	2,6
Particle characteristics:	Not relevant (liquid)

9.2 Other information

9.2.1. Information with regard to physical hazard classes

Not relevant.

9.2.2 Other safety characteristics

Not relevant.

SECTION 10. STABILITY AND REACTIVITY

10.1 Reactivity

The product is not reactive under normal conditions.

10.2 Chemical stability

The product is stable under normal conditions.

10.3 Possibility of hazardous reactions

None known.

10.4 Conditions to avoid

None specific.

10.5 Incompatible materials

Avoid strong acids and bases.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11. TOXIKOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if swallowed.

Ethane-1,2-diol	LD, Oral, Human, ca 1600 mg /kg LD ₅₀ Dermal Rabbit: < 2000 mg/kg
-----------------	---

Kylarväska Super FBL

Corrosive / irritating on the skin

Causes degreasing. May cause mild skin irritation. Ethane-1,2-diol can easily be absorbed through the skin.

Serious eye damage / irritation

May cause mild eye irritation.

Respiratory / skin sensitization

Not considered to be sensitizing.

Germ cell mutagenicity

Not considered to be cause mutations in germ cells.

Carcinogenicity

Not considered to be carcinogenic.

Toxic to reproduction

Not considered to be toxic to reproduction.

Contains small amounts of disodium tetraborate that may damage fertility or the unborn child and sodium 2-ethylhexanoate that is suspected of damaging the unborn child.

Specific organ toxicity-single exposure

The vapours may cause dizziness, drowsiness and headache, at high concentrations. Ingestion of the product affects the kidneys and the central nervous system.

Specific organ toxicity-repeated exposure

May cause damage to organs (kidney) through prolonged or repeated exposure. May cause headache, dizziness, nausea, vomiting, confusion and in serious cases, unconsciousness.

Aspiration Hazard

Not considered to be an aspiration hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Based on available information, this mixture contains no substance which is identified as having endocrine disrupting properties according to Regulation (EU) 2017/2100 or (EU) 2018/605 in concentrations $\geq 0.1\%$ (w/w).

SECTION 12. ECOLOGICAL INFORMATION

The product is not classified as hazardous to the environment.

12.1 Toxicity

Ethane-1,2-diol

LC₅₀ Fish 96 h: 72 860 mg/L (Pimephales promelas)

EC₅₀ Daphnia 48 h: >100 mg/L (Daphnia magna)

IC₅₀ Algae 72 h: 6 500 – 13 000 mg/L (Selenastrum capricornutum)

Kylarväska Super FBL

12.2 Persistence and degradability

Degradability > 70% DOC (28 d) (OECD 301A)

Readily biodegradable

12.3 Bioaccumulative potential

Low potential for bioaccumulation.

12.4 Mobility in soil

The product is soluble in water and is considered to be mobile in soil.

12.5 Results of PBT och vPvB assessment

Based on available information, this mixture contains no substance that meets the PBT or vPvB criteria according to Annex XIII to Regulation (EC) No. 1907/2006 (REACH).

12.6 Endocrine disrupting properties

Based on available information, this mixture contains no substance which is identified as having endocrine disrupting properties according to Regulation (EU) 2017/2100 or (EU) 2018/605 in concentrations $\geq 0.1\%$ (w/w).

12.7 Other adverse effects

None known.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Product residues, spills etc. are classified as hazardous waste. Disposal, transportation, storage and handling of the waste must be in accordance with national regulations. Product waste must not be allowed to contaminate soil or water, or released into the environment.

Prevent discharge into drains.

Classified as hazardous waste, with hazard class HP 5 (Specific Target Organ Toxicity (STOT)/Aspiration Toxicity) och HP 6 (Acute Toxicity).

Suggested waste code (EWC): 16 01 14* antifreeze fluids containing dangerous substances.

Packaging

EWC-code: 15 01 02, Plastic packaging

EWC-code: 15 01 04, Metallic packaging

Packaging containing product residues that are not drip dry must be handled as hazardous waste and disposed of properly sealed.

EWC-code: 15 01 10*, Packaging containing residues of or contaminated by hazardous substances.

SECTION 14. TRANSPORT INFORMATION

The product is not covered by the regulations for the transport of dangerous goods.

Kylarväska Super FBL

	ADR/RID	ADN	IMDG	IATA /ICAO
14.1 UN-number or ID number	N/A	N/A	N/A	N/A
14.2 UN proper shipping name	N/A	N/A	N/A	N/A
14.3 Transport hazard class	N/A	N/A	N/A	N/A
14.4 Packing group	N/A	N/A	N/A	N/A
14.5 Environmental hazards	N/A	N/A	N/A	N/A

14.6 Special precautions for user

Not applicable.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety data sheet is prepared in accordance with the EUROPEAN PARLIAMENT AND COUNCIL REGULATION (EC) No 1907/2006 of 18 December 2006 concerning the registration, evaluation, authorization and restriction of chemicals (REACH) and Commission Regulation (EU) No 2020/878 of 18 June 2020 amending the European Parliament and Council Regulation (EC) No 1907/2006 on the registration, evaluation, authorization and restriction of chemicals (REACH).

Regulations

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substance and mixtures (CLP).

Commission Regulation (EU) No 1357/2014 of 18 December 2014 replacing Annex III to Directive 2008/98/EC of the European Parliament and of the Council on waste.

Sweden

AFS 2011:19, amended by AFS 2018:2 (Chemical risks at work)
AFS 2018:1 (Occupational exposure limits)
KIFS 2017:7 (Chemical products and Biotechnological organisms Regulation)

Finland

654/2020 (Occupational exposure limits)
715/2001 (Chemical risks at work)

Kylarväska Super FBL

Norway

Regulations concerning the design and layout of workplaces and work premises (the Workplace Regulations)

Regulations concerning action and limit values for physical and chemical agents in the working environment and classified biological agents (Regulations concerning Action and Limit values)

Norwegian Product declaration number: 651178

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16. OTHER INFORMATION

Please note! This safety data sheet is an English translation applicable for Sweden, Norway and Finland. A safety data sheet in local language is also available. Please refer to the Agro Oil webshop for safety data sheets in local languages. <https://webshop.agrol.se/>

Classification procedure

Test data is prioritized when classifying the product. When no test data are available the classification criteria in Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures (CLP) have been used.

Hazard statements in Section 3

H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H360FD	May damage fertility. May damage the unborn child.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs (kidney) through prolonged or repeated exposure.

Abbreviations

ADN	International Carriage of Dangerous Goods by Inland Waterways
ADR	International Carriage of Dangerous Goods by Road
BCF	Bio Concentration Factor
BOD5/COD	Biological Oxygen Demand 5 days/Chemical Oxygen demand
BOD (MITI)	Biological Oxygen Demand
DNEL	Derived No Effect Level
EC ₅₀	Effective Concentration (concentration that gives response in 50% of test subjects)
ECHA	European Chemical Agency
EmS	Emergency Schedule Information
HTP	Exposure value, concentrations of impurities in workplace air known to be harmful.
IARC	International Agency for Research on Cancer
IATA/ICAO	IATA Dangerous goods regulation / ICAO Technical Instructions for the Safe Transport of Dangerous Goods by Air
IC ₅₀	Inhibitory Concentration (concentration that shows inhibition in 50% of the test subjects)
IMDG	International Maritime Dangerous Goods Code
KTV	Short term exposure values, normally 15 minutes
LC ₅₀	Lethal Concentration (concentration causing the death of 50% of a group of test animals)
LD ₅₀	Lethal Dose (dose causing the death of 50% of a group of test animals)

Kylarväska Super FBL

Log Pow	Partition coefficient of octanol - water
MITI	Ministry of International Trade and Industry, Japan
NGV	Long term exposure value, normally 8 hours.
NOEC	No Observed Effect Concentration
NOAEC	No Observed Adverse Effect Concentration
NOAEL	No Observed Adverse Effect Level
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bio-accumulative and Toxic substance
PNEC	Predicted No Effect Concentration
RID	International Carriage of Dangerous Goods by Rail
STEL	Short Term Exposure Limit
SVHC	Substance of Very High Concern
TWA	Time-weighted average
vPvB	very Persistent and very Bioaccumulative

Advice on education

The user of this product should have training that is relevant to the properties of the product and relevant use.

References

Information from the supplier: SDS in Swedish, 2021-08-26
Classification & Labelling Inventory Database, ECHA.
Registered substances, ECHA.

Version description

The information has been modified under the following sections in the safety data sheet: 3, 15, 16
The safety data sheet is dated 29.04.2022 and replaces the version dated 01.12.2021.